



Product Number: 20537
Order Abbreviation: CF9DD/827/RP/ECO
General Description: DULUX 9W double compact fluorescent lamp with 2-pin base, 2700K color temperature, 82 CRI, in retail package, ECOLOGIC for use on magnetic ballast

Product Information	
Abbrev. With Packaging Info.	CF9DD827RPECO 10/CS 1/SKU
Average Rated Life (hr)	10000
Base	G23-2
Bulb	D (T4)
Color Rendering Index (CRI)	82
Color Temperature/CCT (K)	2700
Family Brand Name	Dulux® D
Industry Standards	ANSI C78.901 - 2001
Mean Lumens at 25C	452
Maximum Overall Length - MOL (in)	4.3
Maximum Overall Length - MOL (mm)	110
Nominal Wattage (W)	9.00



Footnotes
<p>Approximate initial lumens after 100 hours operation.</p> <p>2 pin CF lamps are not suitable for use in frequently cycled applications or with occupancy sensors. 2 pin CF lamps should never be installed in 4 pin sockets regardless if lamp will fit.</p> <p>SYLVANIA ECOLOGIC fluorescent lamps are designed to pass the Federal Toxic Characteristic Leaching Procedure (TCLP) criteria for classification as non-hazardous waste in most states. TCLP test results are available upon request. Lamp disposal regulations may vary, check your local & state regulations. For more information, please visit www.lamprecycle.org</p>

2 pin CF lamps should never be installed in 4 pin sockets regardless if lamp will fit.

The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.

Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output.

Minimum starting temperature: CF5: -22 degrees F; CF7: -4 degrees F; CF9: 14 degrees F; CF13DS: 14 degrees F; CF13DD: -4 degrees F; CF18DD: 5 degrees F; CF18DT: -4 degrees F; CF26: 14 degrees F.
