



Product Number: 29116
Order Abbreviation: CF13EL/MINITWIST/BL/1
General Description: DULUX 13W mini twist spiral compact fluorescent lamp with integral 120V ballast, medium screw base, 3000K color temperature, 82 CRI

Product Information	
Abbrev. With Packaging Info.	CF13ELMINITWISTBL1 120V 6/CS 1/SKU
Average Rated Life (hr)	8000
Base	Medium
Bulb	MINITWIST
Color Rendering Index (CRI)	82
Color Temperature/CCT (K)	3000
Diameter (in)	1.85
Diameter (mm)	47
Family Brand Name	Dulux® EL
Initial Lumens at 25C	800
Mean Lumens at 25C	640
Maximum Overall Length - MOL (in)	4.5
Maximum Overall Length - MOL (mm)	115
Nominal Voltage (V)	120.00
Nominal Wattage (W)	13.00



Footnotes

Approximate initial lumens after 100 hours operation.

Minimum starting temperature for DULUX EL lamps is 0° F, unless otherwise specified in product literature. .

DULUX ELs meet CSA, FCC and UL requirements.

Caution: DULUX EL units cannot be used on dimming circuits, emergency exit fixtures or lights, electronic timers, photocells, lighted switches or any other switches that do not meet UL20 Sec. 7.6.15. In outdoor applications, use only in enclosed fixtures to avoid exposure to weather. Use only on 120V, 60 Hz circuits. Never disassemble or modify lamp. Install or remove unit from fixture by grasping plastic base. Best performance achieved when operated at 77degrees F (25 degrees C). 40 Watt lamp is designed for base down orientation only.

The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.

Minimum starting temperature for DULUX EL lamps is 0 degrees F

Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output.